

Klübersynth CFH 2-400

Special high-temperature oil for sliding chain systems operating at very high speeds in biaxial film stretchers made by Brückner Maschinenbau



Your benefits at a glance

- Especially developed for high-performance film stretchers
- Very low residue formation even under extreme operating conditions
- Extremely low residue formation minimises need for component maintenance
- Long chain life due to low wear rate
- High equipment economy due to optimised availability especially at high speeds
- Low friction reduces temperature in the chain system

Your requirements - our solution

Operators of film stretchers attach great importance to machine availability and performance to secure profitable production. High-speed stretchers made for large-volume film production have a particular requirement for special chain oils.

For a film stretcher to offer good productivity over a long period of time, the chain oil used must have good backflow characteristics and a very low tendency to form residues. After all, it is often oil residues that lead to more friction and hence higher lubricant consumption. This will in turn lead to further contamination, making premature cleaning of the whole machine (TDO) necessary - a costly and time-consuming procedure. Downtime is inevitable, leading to less machine availability.

Our aim is therefore to maximise machine performance while minimising maintenance and the associated costs.

Klübersynth CFH 2-400 was especially developed for film stretchers involving chain speeds of more than 450 m/min and oven temperatures in excess of 200 °C. Over 40 years of cooperation and partnership with film stretcher OEMs such as Brückner Maschinenbau and operators has helped us build sound technical expertise in the development of high-temperature chain oils.

Klübersynth CFH 2-400 offers you an ideal solution for the continuous operation of film stretchers at very high speeds. This product is a new development and the first to contain a special combination of selected ester oils and additives.

With this raw material combination, Klübersynth CFH 2-400 considerably reduces the formation and adhesion of residues in the chain system. As a result, the friction points can be supplied with sufficient lubricant for many months or even years. Moreover, machine availability increases due to a lower need for cleaning. Klübersynth CFH 2-400 therefore offers film stretcher operators high machine availability and high cost

efficiency, extreme performance and high profitability. This makes it the most powerful product in our successful series of chain oils.

Application

Klübersynth CFH 2-400 is a fully synthetic high-temperature oil that was especially developed for the requirements of conveyor chain sliding systems and pins in biaxial high-speed film stretchers running at speeds > 450 m/min. Oven temperatures may be higher than 200 °C in these applications.

Application notes

Klübersynth CFH 2-400 is miscible with all Klüber chain oils (except PRIMIUM FLUID SPECIAL) offered for biaxial film stretchers. It is therefore not necessary to use a special cleaning or flushing oil for an oil changeover. We recommend, however, to clean the chain system and all machine parts in contact with the oil before filling in the new lubricant so that it can unfold its full benefits. For this purpose, we recommend using our chain cleaning and lubricating oil Klübersynth CZ 2-85.

When changing over from chain oils made by other manufacturers, please ask for advice.

Material safety data sheets

Material safety data sheets can be requested via our website www.klueber.com. You may also obtain them through your contact person at Klüber Lubrication.



Klübersynth CFH 2-400

Special high-temperature oil for sliding chain systems operating at very high speeds in biaxial film stretchers made by Brückner Maschinenbau

Pack sizes	Klübersynth CFH 2-400
Canister 20 l	+
Drum 200 l	+

Product data	Klübersynth CFH 2-400
Article number	002153
NSF-H2 registration	145 154
Chemical composition, type of oil	ester oil
Upper service temperature	250 °C / 482 °F
Colour space	yellow
Appearance	clear
Flash point, DIN EN ISO 2592, Cleveland, open-cup apparatus	>= 270 °C
Kinematic viscosity, DIN 51562 pt. 01/ASTM D-445/ASTM D 7042, 40 °C	approx. 400 mm ² /s
Kinematic viscosity, DIN 51562 pt. 01/ASTM D-445/ASTM D 7042, 100 °C	approx. 25 mm ² /s
Viscosity index, DIN ISO 2909	>= 75
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	36 months

Klüber Lubrication – your global specialist

Innovative tribological solutions are our passion. Through personal contact and consultation, we help our customers to be successful worldwide, in all industries and markets. With our ambitious technical concepts and experienced, competent staff we have been fulfilling increasingly demanding requirements by manufacturing efficient high-performance lubricants for more than 80 years.

Klüber Lubrication München SE & Co. KG / Geisenhausenerstraße 7 / 81379 München / Germany / phone +49 89 7876-0 / fax +49 89 7876-333.

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication München SE & Co. KG. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München SE & Co. KG and if source is indicated and voucher copy is forwarded.