

# Safety Data Sheet according to (EC) No 1907/2006

LOCTITE SI 5366 CL known as 5366 CLEAR 310ML GB

Page 1 of 9

SDS No.: 164436

V006.1

Revision: 26.05.2015

printing date: 05.04.2016

Replaces version from: 09.01.2015

Category 2

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

LOCTITE SI 5366 CL known as 5366 CLEAR 310ML GB

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Silicone sealant

# ${f 1.3.}$ Details of the supplier of the safety data sheet

Henkel Ltd Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000 Fax-no.: +44 1442 278071

ua-productsafety.uk@uk.henkel.com

### 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### Classification (CLP):

Skin irritation

H315 Causes skin irritation.

Serious eye irritation Category 2

H319 Causes serious eye irritation.

### 2.2. Label elements

#### Label elements (CLP):

Hazard pictogram:



Signal word: Warning

**Hazard statement:** H315 Causes skin irritation.

H319 Causes serious eye irritation.

LOCTITE SI 5366 CL known as 5366 CLEAR 310ML GB

Page 2 of 9

MSDS-No.: 164436

V006.1

**Precautionary statement:** P302+P352 IF ON SKIN: Wash with plenty of water.

**Response** P337+P313 If eye irritation persists: Get medical advice/attention.

### 2.3. Other hazards

None if used properly.

### **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

### General chemical description:

Acetoxy curing silicone

#### Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Acetic acid 64-19-7	200-580-7 01-2119475328-30	>= 1-< 3 %	Skin Corr. 1A H314 Flam. Liq. 3 H226
Methyltriacetoxysilane 4253-34-3	224-221-9 01-2119962266-32	>= 1-< 3 %	Acute Tox. 4; Oral H302 Skin Corr. 1B H314

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

Acetic acid is liberated slowly upon contact with moisture.

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eve contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

SKIN: Redness, inflammation.

EYE: Irritation, conjunctivitis.

#### 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

### **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media Suitable extinguishing media:

Carbon dioxide, foam, powder

Fine water spray

#### Extinguishing media which must not be used for safety reasons:

None known

#### 5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus.

### Additional information:

In case of fire, keep containers cool with water spray.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Ensure adequate ventilation.

#### 6.2. Environmental precautions

Do not let product enter drains.

#### 6.3. Methods and material for containment and cleaning up

Scrape up as much material as possible.

Ensure adequate ventilation.

Store in a partly filled, closed container until disposal.

Dispose of contaminated material as waste according to Section 13.

#### 6.4. Reference to other sections

See advice in section 8

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Use only in well-ventilated areas.

Vapours should be extracted to avoid inhalation.

See advice in section 8

#### Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

### 7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, well-ventilated place.

Refer to Technical Data Sheet

Never allow product to get in contact with water during storage

#### 7.3. Specific end use(s)

Silicone sealant

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

# **Occupational Exposure Limits**

Valid for

Great Britain

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Acetic acid	10	25	Time Weighted Average	Indicative	ECTLV
64-19-7			(TWA):		
[ACETIC ACID]					

# **Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment	•	Value	Value			Remarks
			mg/l	ppm	mg/kg	others	
Acetic acid 64-19-7	aqua (freshwater)					3,058 mg/L	
Acetic acid 64-19-7	Soil				0,478 mg/kg		
Acetic acid 64-19-7	STP					85 mg/L	
Acetic acid 64-19-7	sediment (freshwater)				11,36 mg/kg		

# **Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Acetic acid 64-19-7	Workers	inhalation	Acute/short term exposure - local effects		25 mg/m3	
Acetic acid 64-19-7	general population	inhalation	Acute/short term exposure - local effects		25 mg/m3	
Acetic acid 64-19-7	Workers	inhalation	Long term exposure - local effects		25 mg/m3	
Acetic acid 64-19-7	general population	inhalation	Long term exposure - local effects		25 mg/m3	

### **Biological Exposure Indices:**

None

### 8.2. Exposure controls:

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eve protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Skin protection:

Wear suitable protective clothing.

### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Appearance paste

Clear

Odor Acetic acid

Odour threshold No data available / Not applicable

pH Not applicable
Initial boiling point Not determined
Flash point > 150 °C (> 302 °F)

Decomposition temperature No data available / Not applicable

Vapour pressure < 0.1 mm hgDensity 1,04 g/cm3

0

Bulk density

No data available / Not applicable
Viscosity

No data available / Not applicable
Viscosity (kinematic)

No data available / Not applicable
Explosive properties

No data available / Not applicable

Solubility (qualitative) Partially soluble

(Solvent: Water)

Solubility (qualitative) Insoluble

(Solvent: Acetone)

Solidification temperature No data available / Not applicable Melting point No data available / Not applicable No data available / Not applicable Flammability Auto-ignition temperature No data available / Not applicable **Explosive limits** No data available / Not applicable No data available / Not applicable Partition coefficient: n-octanol/water No data available / Not applicable Evaporation rate Vapor density No data available / Not applicable Oxidising properties No data available / Not applicable

#### 9.2. Other information

No data available / Not applicable

### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Strong oxidizing agents.

Polymerises in presence of water.

### 10.2. Chemical stability

Stable under recommended storage conditions.

MSDS-No.: 164436

V006.1

#### 10.3. Possibility of hazardous reactions

See section reactivity

#### 10.4. Conditions to avoid

No decomposition if used according to specifications.

#### 10.5. Incompatible materials

See section reactivity

#### 10.6. Hazardous decomposition products

Acetic acid is liberated slowly upon contact with moisture.

At higher temperatures (>150C) may release formaldehyde (traces).

## **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

#### General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

#### Oral toxicity:

This material is considered to have low toxicity if swallowed.

#### Inhalative toxicity:

Acetic acid is liberated slowly upon contact with moisture.

Inhalation of vapors in high concentration may cause irritation of respiratory system

#### Skin irritation:

Causes skin irritation.

#### Eye irritation:

Acetic acid released during polymerisation of acetoxy curing RTV silicones is irritating to the eyes Causes serious eye irritation.

#### Acute oral toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Acetic acid	LD50	3.310 mg/kg	oral		rat	
64-19-7						
Methyltriacetoxysilane	LD50	1.600 mg/kg	oral		rat	OECD Guideline 401 (Acute
4253-34-3						Oral Toxicity)

### Germ cell mutagenicity:

Hazardous components	Result	Type of study /	Metabolic	Species	Method
CAS-No.		Route of	activation /		
		administration	Exposure time		
Acetic acid	negative	bacterial reverse	with and without		OECD Guideline 471
64-19-7		mutation assay (e.g			(Bacterial Reverse Mutation
		Ames test)			Assay)
	negative	in vitro mammalian	with and without		OECD Guideline 473 (In vitro
		chromosome			Mammalian Chromosome
		aberration test			Aberration Test)

V006.1

MSDS-No.: 164436

### **SECTION 12: Ecological information**

#### **General ecological information:**

Cured Loctite products are typical polymers and do not pose any immediate environmental hazards.

In the cured state contribution of this product to Environmental Hazards is insignificant in comparison to articles in which it is used.

Precautions required with respect to Environmental Hazards of articles in which this product is used should be considered. The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

### 12.1. Toxicity

#### **Ecotoxicity:**

Do not empty into drains / surface water / ground water.

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Acetic acid 64-19-7	LC50	410 mg/l	Fish	48 h	Leuciscus idus melanotus	OECD Guideline 203 (Fish, Acute Toxicity Test)
Acetic acid 64-19-7	EC50	6.000 mg/l	Daphnia	24 h	Daphnia magna	
Acetic acid 64-19-7	EC50	> 4.000 mg/l	Algae	8 d	Scenedesmus quadricauda	OECD Guideline 201 (Alga, Growth Inhibition Test)

### 12.2. Persistence and degradability

#### Persistence and Biodegradability:

The product is not biodegradable.

	Hazardous components CAS-No.	Result	Route of application	Degradability	Method
ſ	Acetic acid	readily biodegradable	aerobic	89 - 99 %	EU Method C.4-E (Determination
	64-19-7				of the "Ready"
					BiodegradabilityClosed Bottle
					Test)

#### 12.3. Bioaccumulative potential / 12.4. Mobility in soil

#### **Mobility:**

Cured adhesives are immobile.

#### **Bioaccumulative potential:**

Does not bioaccumulate.

Hazardous components CAS-No.	LogKow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Acetic acid 64-19-7	-0,17					

# 12.5. Results of PBT and vPvB assessment

Hazardous components	PBT/vPvB
CAS-No.	
Acetic acid	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
64-19-7	Bioaccumulative (vPvB) criteria.

### 12.6. Other adverse effects

No data available.

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

V006.1

Product disposal:

MSDS-No.: 164436

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

#### Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

### **SECTION 14: Transport information**

#### 14.1. UN number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

#### 14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

### 14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

#### 14.4. Packaging group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

#### 14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

#### 14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

### **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content (1999/13/EC) < 3 %

#### 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

### **SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapor.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

#### **Further information:**

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

#### Label elements (DPD):

The product is not subject to classification according to the calculation methods of the "General Classification Guideline for Preparations of the EC" as issued in the last version.

#### Additional labeling:

Safety data sheet available for professional user on request.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.