

MOLYKOTE(R) HSC PLUS PASTE

Version	Revision Date:	SDS Number:	Date of last issue: 11.11.2015
2.3	19.03.2016	659420-00006	Date of first issue: 22.10.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : MOLYKOTE(R) HSC PLUS PASTE

Product code : 000000000002286921, 000000000002286921

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Lubricants and lubricant additives

1.3 Details of the supplier of the safety data sheet

Company : Dow Corning Europe S.A.
rue Jules Bordet - Parc Industriel - Zone C
B-7180 Seneffe

PO box : 65091

Telephone : English Tel: +49 611237507
Deutsch Tel: +49 611237500
Français Tel: +32 64511149
Italiano Tel: +32 64511170
Español Tel: +32 64511163

E-mail address of person
responsible for the SDS : sdseu@dowcorning.com

1.4 Emergency telephone number

Dow Corning (Barry U.K. 24h) Tél: +44 1446732350
Dow Corning (Wiesbaden 24h) Tél: +49 61122158
Dow Corning (Seneffe 24h) Tel: +32 64 888240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute aquatic toxicity, Category 1	H400: Very toxic to aquatic life.
Chronic aquatic toxicity, Category 1	H410: Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

MOLYKOTE(R) HSC PLUS PASTE

Version	Revision Date:	SDS Number:	Date of last issue: 11.11.2015
2.3	19.03.2016	659420-00006	Date of first issue: 22.10.2014

Hazard pictograms :



Signal word : Warning

Hazard statements : H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements :
Prevention:
P273 Avoid release to the environment.
Response:
P391 Collect spillage.

2.3 Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Inorganic and organic compounds
Mixture

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Copper metal powder	7440-50-8 231-159-6	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 20 - < 25
Paraffin oil	8012-95-1 232-384-2	Asp. Tox. 1; H304	>= 20 - < 30
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0 265-169-7	Asp. Tox. 1; H304	>= 10 - < 20
Substances with a workplace exposure limit :			
Tin	7440-31-5 231-141-8		>= 10 - < 20

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

Protection of first-aiders : No special precautions are necessary for first aid responders.

If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.

MOLYKOTE(R) HSC PLUS PASTE

Version	Revision Date:	SDS Number:	Date of last issue: 11.11.2015
2.3	19.03.2016	659420-00006	Date of first issue: 22.10.2014

In case of skin contact	:	Wash with water and soap as a precaution. Get medical attention if symptoms occur.
In case of eye contact	:	Flush eyes with water as a precaution. Get medical attention if irritation develops and persists.
If swallowed	:	If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment	:	Treat symptomatically and supportively.
-----------	---	---

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	:	Water spray Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
------------------------------	---	--

Unsuitable extinguishing media	:	None known.
--------------------------------	---	-------------

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting	:	Exposure to combustion products may be a hazard to health.
---------------------------------------	---	--

Hazardous combustion products	:	Carbon oxides Nitrogen oxides (NO _x) Metal oxides Sulphur oxides Oxides of phosphorus
-------------------------------	---	---

5.3 Advice for firefighters

Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.
---	---	---

Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
--------------------------------	---	---

MOLYKOTE(R) HSC PLUS PASTE

Version	Revision Date:	SDS Number:	Date of last issue: 11.11.2015
2.3	19.03.2016	659420-00006	Date of first issue: 22.10.2014

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Follow safe handling advice and personal protective equipment recommendations.

6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice.
Take care to prevent spills, waste and minimize release to the environment.

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage : Keep in properly labelled containers. Store in accordance with

MOLYKOTE(R) HSC PLUS PASTE

Version	Revision Date:	SDS Number:	Date of last issue: 11.11.2015
2.3	19.03.2016	659420-00006	Date of first issue: 22.10.2014

areas and containers the particular national regulations.

Advice on common storage : Do not store with the following product types:
Strong oxidizing agents

7.3 Specific end use(s)

Specific use(s) : These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Copper metal powder	7440-50-8	TWA (Fumes)	0.2 mg/m ³ (Copper)	GB EH40
		TWA (Dusts and mists)	1 mg/m ³ (Copper)	GB EH40
		STEL (Dusts and mists)	2 mg/m ³ (Copper)	GB EH40
Tin	7440-31-5	TWA	2 mg/m ³ (Tin)	91/322/EEC
Further information	Indicative, Existing scientific data on health effects appear to be particularly limited			
		TWA	2 mg/m ³ (Tin)	GB EH40
		STEL	4 mg/m ³ (Tin)	GB EH40
Molybdenum sulfide	1317-33-5	TWA	10 mg/m ³ (Molybdenum)	GB EH40
		STEL	20 mg/m ³ (Molybdenum)	GB EH40

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Tin	Workers	Inhalation	Long-term systemic effects	11.75 mg/m ³
	Workers	Inhalation	Acute systemic effects	11.75 mg/m ³
	Workers	Skin contact	Long-term systemic effects	133.3 mg/kg bw/day
	Workers	Skin contact	Acute systemic effects	133.3 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	3.476 mg/m ³
	Consumers	Inhalation	Acute systemic effects	3.476 mg/m ³

MOLYKOTE(R) HSC PLUS PASTE

Version 2.3 Revision Date: 19.03.2016 SDS Number: 659420-00006 Date of last issue: 11.11.2015
Date of first issue: 22.10.2014

	Consumers	Skin contact	Long-term systemic effects	80 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	80 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	80 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	80 mg/kg bw/day
Paraffin oil	Workers	Inhalation	Long-term systemic effects	5 mg/m3
	Workers	Inhalation	Short-term exposure	5 mg/m3
	Workers	Inhalation	Long-term local effects	5 mg/m3
	Workers	Inhalation	Acute local effects	5 mg/m3
Copper metal powder	Consumers	Inhalation	Acute systemic effects	20 mg/m3
	Consumers	Skin contact	Acute systemic effects	137 mg/kg bw/day
	Workers	Skin contact	Long-term systemic effects	137 mg/kg bw/day
	Workers	Inhalation	Acute systemic effects	20 mg/m3
	Workers	Skin contact	Acute systemic effects	273 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	137 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Copper metal powder	Fresh water	7.8 µg/l
	Marine water	5.2 µg/l
	Sewage treatment plant	230 µg/l
	Fresh water sediment	87 mg/kg
	Marine sediment	676 mg/kg
	Soil	65 mg/kg

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Eye protection : Wear the following personal protective equipment:
Safety glasses

Hand protection
Remarks : Wash hands before breaks and at the end of workday.

Skin and body protection : Skin should be washed after contact.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

MOLYKOTE(R) HSC PLUS PASTE

Version	Revision Date:	SDS Number:	Date of last issue: 11.11.2015
2.3	19.03.2016	659420-00006	Date of first issue: 22.10.2014

Filter type : Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: paste
Colour	: bronze
Odour	: none
Odour Threshold	: No data available
pH	: Not applicable
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: Not applicable
Flash point	: Not applicable
Evaporation rate	: Not applicable
Flammability (solid, gas)	: Not classified as a flammability hazard
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: Not applicable
Relative vapour density	: No data available
Relative density	: 1.30
Solubility(ies)	
Water solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: Not applicable
Explosive properties	: Not explosive

MOLYKOTE(R) HSC PLUS PASTE

Version	Revision Date:	SDS Number:	Date of last issue: 11.11.2015
2.3	19.03.2016	659420-00006	Date of first issue: 22.10.2014

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Molecular weight : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Can react with strong oxidizing agents.
When heated to temperatures above 150 °C (300 °F) in the presence of air, product can form formaldehyde vapours. Safe handling conditions may be maintained by keeping vapour concentrations within the occupational exposure limit for formaldehyde.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Copper metal powder:

Acute oral toxicity : LD50 (Rat): > 2,500 mg/kg
Method: OECD Test Guideline 423
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 5.11 mg/l

MOLYKOTE(R) HSC PLUS PASTE

Version 2.3	Revision Date: 19.03.2016	SDS Number: 659420-00006	Date of last issue: 11.11.2015 Date of first issue: 22.10.2014
----------------	------------------------------	-----------------------------	---

Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 436

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Paraffin oil:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

Tin:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 4.75 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Not classified based on available information.

MOLYKOTE(R) HSC PLUS PASTE

Version	Revision Date:	SDS Number:	Date of last issue: 11.11.2015
2.3	19.03.2016	659420-00006	Date of first issue: 22.10.2014

Components:

Copper metal powder:

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

Paraffin oil:

Species: Rabbit
Result: No skin irritation

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species: Rabbit
Result: No skin irritation
Remarks: Based on data from similar materials

Tin:

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Copper metal powder:

Species: Rabbit
Method: OECD Test Guideline 405
Result: No eye irritation

Paraffin oil:

Species: Rabbit
Result: No eye irritation

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species: Rabbit
Method: OECD Test Guideline 405
Result: No eye irritation
Remarks: Based on data from similar materials

Tin:

Species: Rabbit
Method: OECD Test Guideline 405
Result: No eye irritation

MOLYKOTE(R) HSC PLUS PASTE

Version	Revision Date:	SDS Number:	Date of last issue: 11.11.2015
2.3	19.03.2016	659420-00006	Date of first issue: 22.10.2014

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Copper metal powder:

Test Type: Maximisation Test
Exposure routes: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406
Result: negative

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Test Type: Buehler Test
Exposure routes: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406
Result: negative
Remarks: Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Components:

Copper metal powder:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Ingestion Method: Directive 67/548/EEC, Annex V, B.12. Result: negative Remarks: Based on data from similar materials

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative Remarks: Based on data from similar materials
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection

MOLYKOTE(R) HSC PLUS PASTE

Version	Revision Date:	SDS Number:	Date of last issue: 11.11.2015
2.3	19.03.2016	659420-00006	Date of first issue: 22.10.2014

Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Tin:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species: Mouse
Application Route: Skin contact
Exposure time: 78 weeks
Method: OECD Test Guideline 451
Result: negative

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

Tin:

Species: Rat
Application Route: Ingestion
Exposure time: 115 weeks
Result: negative
Remarks: Based on data from similar materials

Reproductive toxicity

Not classified based on available information.

Components:

Copper metal powder:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rabbit
Application Route: Ingestion
Result: negative

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test

MOLYKOTE(R) HSC PLUS PASTE

Version 2.3	Revision Date: 19.03.2016	SDS Number: 659420-00006	Date of last issue: 11.11.2015 Date of first issue: 22.10.2014
----------------	------------------------------	-----------------------------	---

Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Skin contact
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

Tin:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 421
Result: negative

Effects on foetal development : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 421
Result: negative

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

Copper metal powder:

Exposure routes: inhalation (dust/mist/fume)

Assessment: No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

Repeated dose toxicity

Components:

Copper metal powder:

Species: Rat

NOAEL: ≥ 2 mg/m³

Application Route: inhalation (dust/mist/fume)

Exposure time: 28 Days

Paraffin oil:

Species: Rat, female

MOLYKOTE(R) HSC PLUS PASTE

Version	Revision Date:	SDS Number:	Date of last issue: 11.11.2015
2.3	19.03.2016	659420-00006	Date of first issue: 22.10.2014

LOAEL: 161 mg/kg
Application Route: Ingestion
Exposure time: 90 Days

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species: Rabbit
NOAEL: 1,000 mg/kg
Application Route: Skin contact
Exposure time: 4 Weeks
Method: OECD Test Guideline 410
Remarks: Based on data from similar materials

Species: Rat
NOAEL: > 980 mg/m³
Application Route: inhalation (dust/mist/fume)
Exposure time: 4 Weeks
Remarks: Based on data from similar materials

Tin:

Species: Rat
NOAEL: > 1,000 mg/kg
Application Route: Ingestion
Exposure time: 28 Days
Method: OECD Test Guideline 407

Aspiration toxicity

Not classified based on available information.

Components:

Paraffin oil:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Copper metal powder:

Toxicity to fish : LC50 : 8.1 µg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 0.792 mg/l
aquatic invertebrates Exposure time: 48 h

MOLYKOTE(R) HSC PLUS PASTE

Version	Revision Date:	SDS Number:	Date of last issue: 11.11.2015
2.3	19.03.2016	659420-00006	Date of first issue: 22.10.2014

Toxicity to algae : EC50 (Chlorella vulgaris (Fresh water algae)): 0.333 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 100

Toxicity to fish (Chronic toxicity) : NOEC: 1 µg/l
Species: Oncorhynchus mykiss (rainbow trout)

M-Factor (Chronic aquatic toxicity) : 100

Paraffin oil:

Toxicity to fish : LL50 (Scophthalmus maximus (turbot)): > 1,028 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Acartia tonsa): > 3,193 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

Toxicity to algae : EL50 (Skeletonema costatum (marine diatom)): > 3,200 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

NOELR (Skeletonema costatum (marine diatom)): 993 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to bacteria : NOEC : > 1.93 mg/l

MOLYKOTE(R) HSC PLUS PASTE

Version	Revision Date:	SDS Number:	Date of last issue: 11.11.2015
2.3	19.03.2016	659420-00006	Date of first issue: 22.10.2014

Exposure time: 10 min
Method: DIN 38 412 Part 8
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 10 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Tin:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 12.4 µg/l
Exposure time: 96 h
Remarks: No toxicity at the limit of solubility
Based on data from similar materials

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 19.2 µg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: No toxicity at the limit of solubility
Based on data from similar materials

Toxicity to bacteria : EC50 : > 511 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 100 µg/l
Exposure time: 7 d
Species: Ceriodaphnia dubia (water flea)
Remarks: No toxicity at the limit of solubility
Based on data from similar materials

12.2 Persistence and degradability

Components:

Paraffin oil:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 82 %
Exposure time: 24 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 8 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

MOLYKOTE(R) HSC PLUS PASTE

Version	Revision Date:	SDS Number:	Date of last issue: 11.11.2015
2.3	19.03.2016	659420-00006	Date of first issue: 22.10.2014

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- | | |
|------------------------|---|
| Product | : Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities. |
| Contaminated packaging | : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product. |

SECTION 14: Transport information

14.1 UN number

- | | |
|------|-----------|
| ADN | : UN 3077 |
| ADR | : UN 3077 |
| RID | : UN 3077 |
| IMDG | : UN 3077 |
| IATA | : UN 3077 |

14.2 UN proper shipping name

- | | |
|------|---|
| ADN | : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(Copper metal powder) |
| ADR | : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(Copper metal powder) |
| RID | : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(Copper metal powder) |
| IMDG | : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(Copper metal powder) |

MOLYKOTE(R) HSC PLUS PASTE

Version	Revision Date:	SDS Number:	Date of last issue: 11.11.2015
2.3	19.03.2016	659420-00006	Date of first issue: 22.10.2014

IATA : Environmentally hazardous substance, solid, n.o.s.
(Copper metal powder)

14.3 Transport hazard class(es)

ADN : 9
ADR : 9
RID : 9
IMDG : 9
IATA : 9

14.4 Packing group

ADN
Packing group : III
Classification Code : M7
Hazard Identification Number : 90
Labels : 9

ADR
Packing group : III
Classification Code : M7
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (E)

RID
Packing group : III
Classification Code : M7
Hazard Identification Number : 90
Labels : 9

IMDG
Packing group : III
Labels : 9
EmS Code : F-A, S-F

IATA (Cargo)
Packing instruction (cargo aircraft) : 956
Packing instruction (LQ) : Y956
Packing group : III
Labels : Miscellaneous

IATA (Passenger)
Packing instruction (passenger aircraft) : 956
Packing instruction (LQ) : Y956
Packing group : III
Labels : Miscellaneous

14.5 Environmental hazards

ADN
Environmentally hazardous : yes

ADR

MOLYKOTE(R) HSC PLUS PASTE

Version 2.3	Revision Date: 19.03.2016	SDS Number: 659420-00006	Date of last issue: 11.11.2015 Date of first issue: 22.10.2014
----------------	------------------------------	-----------------------------	---

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Marine pollutant : yes

IATA (Cargo)

Marine pollutant : yes

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E1	ENVIRONMENTAL HAZARDS	Quantity 1 100 t	Quantity 2 200 t
----	--------------------------	---------------------	---------------------

The components of this product are reported in the following inventories:

KECI : All ingredients listed, exempt or notified.

TSCA : All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

REACH : All ingredients (pre-)registered or exempt.

MOLYKOTE(R) HSC PLUS PASTE

Version	Revision Date:	SDS Number:	Date of last issue: 11.11.2015
2.3	19.03.2016	659420-00006	Date of first issue: 22.10.2014

AICS	: All ingredients listed or exempt.
IECSC	: All ingredients listed or exempt.
PICCS	: All ingredients listed or exempt.
NZIoC	: All ingredients listed or exempt.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Full text of H-Statements

H304	: May be fatal if swallowed and enters airways.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Acute	: Acute aquatic toxicity
Aquatic Chronic	: Chronic aquatic toxicity
Asp. Tox.	: Aspiration hazard
91/322/EEC	: Europe. Commission Directive 91/322/EEC on establishing indicative limit values
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
91/322/EEC / TWA	: Limit Value - eight hours
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Develop-

MOLYKOTE(R) HSC PLUS PASTE

Version	Revision Date:	SDS Number:	Date of last issue: 11.11.2015
2.3	19.03.2016	659420-00006	Date of first issue: 22.10.2014

ment; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN