Regulation 1907/2006/EC

## **AeroShell Turbine Oil 308**

Version 4.0 Revision Date 14.08.2015 Print Date 15.08.2015

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : AeroShell Turbine Oil 308

Product code : 001A0080

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Synthetic lubricating oil for aircraft turbine engines., For further

Substance/Mixture details consult the AeroShell Book on www.shell.com/aviation.

Uses advised against : This product must be used, handled and applied in

accordance with the requirements of the equipment

manufacturer's manuals, bulletins and other documentation. This product must not be used in applications other than those

listed in Section 1 without first seeking the advice of the

supplier.

## 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier : Shell UK Oil Products Limited

Shell Centre London SE1 7NA United Kingdom

Telephone : (+44) 08007318888

Telefax

**Email Contact for Safety Data** 

Sheet

: If you have any enquiries about the content of this SDS

please email lubricantSDS@shell.com

#### 1.4 Emergency telephone number

: +44-(0) 151-350-4595

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Chronic aquatic toxicity, Category 2 H411: Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

## Labelling (REGULATION (EC) No 1272/2008)

Regulation 1907/2006/EC

## **AeroShell Turbine Oil 308**

Version 4.0 Revision Date 14.08.2015 Print Date 15.08.2015

Hazard pictograms



Signal word

ord : Warnin

Hazard statements

PHYSICAL HAZARDS:

Not classified as a physical hazard

according to CLP criteria. HEALTH HAZARDS:

H317

May cause an allergic skin reaction. ENVIRONMENTAL HAZARDS:

H411 Toxic to aquati

Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention:

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

Storage:

No precautionary phrases.

Disposal:

P501

Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

Contains N-phenyl-1-naphthylamine

Sensitising components : Contains 2,6-di-tert-butyl dimethylamino p-cresol.

## 2.3 Other hazards

This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB.

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used oil may contain harmful impurities.

Not classified as flammable but will burn.

## **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Chemical nature : Blend of synthetic esters and additives.

## **Hazardous components**

| Chemical Name | CAS-No. | Classification | Concentration |
|---------------|---------|----------------|---------------|
|               | EC-No.  | (REGULATION    | [%]           |

Version 4.0 Revision Date 14.08.2015 Print Date 15.08.2015

|   | Registration number                            | (EC) No<br>1272/2008)  |       |
|---|--|--|-------|
| Alkaryl amine                                   | 68411-46-1<br>270-128-1 / 01-<br>2119491299-23 | Aquatic Chronic3;<br>H412  | < 5   |
| Triaryl phosphate                               | 1330-78-5<br>215-548-8                         | Repr.2; H361f<br>Aquatic Acute1;<br>H400<br>Aquatic Chronic1;<br>H410  | < 2.4 |
| N-phenyl-1-<br>naphthylamine                    | 90-30-2<br>201-983-0                           | Acute Tox.4; H302<br>Skin Sens.1B;<br>H317<br>STOT RE2; H373<br>Aquatic Acute1;<br>H400<br>Aquatic Chronic1;<br>H410 | < 2.4 |
| 2,6-di-tert-butyl<br>dimethylamino p-<br>cresol | 88-27-7<br>201-816-1                           | Acute Tox.4; H302<br>Skin Sens.1B;<br>H317<br>Eye Irrit.2; H319<br>Aquatic Chronic1;<br>H410                         | <1    |

For explanation of abbreviations see section 16.

## **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

If inhaled : No treatment necessary under normal conditions of use.

If symptoms persist, obtain medical advice.

In case of skin contact : Remove contaminated clothing. Flush exposed area with

water and follow by washing with soap if available.

If persistent irritation occurs, obtain medical attention.

In case of eye contact : Flush eye with copious quantities of water.

If persistent irritation occurs, obtain medical attention.

If swallowed : In general no treatment is necessary unless large quantities

are swallowed, however, get medical advice.

## 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Skin sensitisation (allergic skin reaction) signs and symptoms

may include itching and/or a rash.

Regulation 1907/2006/EC

## **AeroShell Turbine Oil 308**

Version 4.0 Revision Date 14.08.2015 Print Date 15.08.2015

Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Notes to doctor/physician:

Treat symptomatically.

## **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon

dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing : Do not use water in a jet.

media

## 5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

 Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.

## 5.3 Advice for firefighters

Special protective equipment

for firefighters

: Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

## **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : 6.1.1 For non emergency personnel:

Avoid contact with skin and eyes. 6.1.2 For emergency responders: Avoid contact with skin and eyes.

#### 6.2 Environmental precautions

Environmental precautions : Use appropriate containment to avoid environmental

contamination. Prevent from spreading or entering drains,

Regulation 1907/2006/EC

# **AeroShell Turbine Oil 308**

Version 4.0 Revision Date 14.08.2015 Print Date 15.08.2015

ditches or rivers by using sand, earth, or other appropriate

barriers.

Local authorities should be advised if significant spillages

cannot be contained.

## 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Slippery when spilt. Avoid accidents, clean up immediately.

Prevent from spreading by making a barrier with sand, earth

or other containment material.

Reclaim liquid directly or in an absorbent.

Soak up residue with an absorbent such as clay, sand or other

suitable material and dispose of properly.

#### 6.4 Reference to other sections

For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.

## **SECTION 7: Handling and storage**

General Precautions : Use local exhaust ventilation if there is risk of inhalation of

vapours, mists or aerosols.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine

appropriate controls for safe handling, storage and disposal of

this material.

#### 7.1 Precautions for safe handling

Advice on safe handling : Avoid prolonged or repeated contact with skin.

Avoid inhaling vapour and/or mists.

When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning

materials in order to prevent fires.

Product Transfer : This material has the potential to be a static accumulator.

Proper grounding and bonding procedures should be used

during all bulk transfer operations.

## 7.2 Conditions for safe storage, including any incompatibilities

Other data : Keep container tightly closed and in a cool, well-ventilated

place. Use properly labeled and closable containers. Must be

stored in a diked (bunded) area.

Storage temperature : -50 - 50 °C

Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

Regulation 1907/2006/EC

## **AeroShell Turbine Oil 308**

Version 4.0 Revision Date 14.08.2015 Print Date 15.08.2015

The storage of this product may be subject to the Control of Pollution (Oil Storage) (England) Regulations. Further guidance may be obtained from the local environmental

agency office.

Packaging material : Suitable material: For containers or container linings, use mild

steel or high density polyethylene.

Unsuitable material: PVC.

Container Advice : Polyethylene containers should not be exposed to high

temperatures because of possible risk of distortion.

7.3 Specific end use(s)

Specific use(s) : Not applicable

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### **Occupational Exposure Limits**

## Biological occupational exposure limits

No biological limit allocated.

## **Monitoring Methods**

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Version 4.0 Revision Date 14.08.2015 Print Date 15.08.2015

## 8.2 Exposure controls

**Engineering measures** The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

#### General Information:

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

#### Personal protective equipment

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : If material is handled such that it could be splashed into eyes,

protective eyewear is recommended. Approved to EU Standard EN166.

Hand protection

Remarks : Where hand contact with the product may occur the use of

gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly

gloves, hands should be washed and dried thoroughly.

Application of a non-perfumed moisturizer is recommended.

For continuous contact we recommend gloves with

breakthrough time of more than 240 minutes with preference

Version 4.0 Revision Date 14.08.2015 Print Date 15.08.2015

for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

Skin and body protection

Wear chemical resistant gloves/gauntlets and boots. Where risk of splashing, also wear an apron.

Respiratory protection

No respiratory protection is ordinarily required under normal conditions of use.

In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne

concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an

appropriate combination of mask and filter.

Select a filter suitable for combined particulate/organic gases and vapours [Type A/Type P boiling point > 65°C (149°F)]

meeting EN14387 and EN143.

Thermal hazards : Not applicable

Hygiene measures : Exposure to this product should be reduced as low as

reasonably practicable. Reference should be made to the

Health and Safety Executive's publication "COSHH

Essentials".

## **Environmental exposure controls**

General advice

: Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Chapter 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water.

Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing

vapour.

Regulation 1907/2006/EC

## **AeroShell Turbine Oil 308**

Version 4.0 Revision Date 14.08.2015 Print Date 15.08.2015

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Appearance : Liquid at room temperature.

Colour : amber

Odour : Slight hydrocarbon
Odour Threshold : Data not available
pH : Not applicable

pour point : <= -62 °CMethod: Unspecified

Initial boiling point and boiling : > 280 °Cestimated value(s)

range

Flash point : 235 °C

Method: Unspecified

Evaporation rate : Data not available Flammability (solid, gas) : Data not available

Upper explosion limit : Typical 10 %(V)

Lower explosion limit : Typical 1 %(V)

Vapour pressure : < 0.5 Pa (20 °C)

estimated value(s)

Relative vapour density : > 1estimated value(s)

Relative density : 0.956 (15 °C)

Density : 956 kg/m3 (15.0 °C)

Method: Unspecified

Solubility(ies)

Water solubility : negligible

Solubility in other solvents : Data not available

Partition coefficient: n-

octanol/water

: Pow: > 6(based on information on similar products)

Auto-ignition temperature : :

320 °C

Viscosity

9 / 20 GB

Regulation 1907/2006/EC

## **AeroShell Turbine Oil 308**

Version 4.0 Revision Date 14.08.2015 Print Date 15.08.2015

Viscosity, dynamic : Data not available Viscosity, kinematic : 12 mm2/s (40.0 °C)

Method: Unspecified

3.1 mm2/s (100 °C) Method: Unspecified

2400 mm2/s (-40 °C) Method: Unspecified

12000 mm2/s (-51.0 °C) Method: Unspecified

Explosive properties : Not classified

Oxidizing properties : Data not available

#### 9.2 Other information

Conductivity : This material is not expected to be a static accumulator.

Decomposition temperature : Data not available

## **SECTION 10: Stability and reactivity**

## 10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

## 10.2 Chemical stability

Stable.

No hazardous reaction is expected when handled and stored according to provisions

## 10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

10.4 Conditions to avoid

Conditions to avoid : Extremes of temperature and direct sunlight.

10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

## 10.6 Hazardous decomposition products

Hazardous decomposition : Hazardous decomposition products are not expected to form

products during normal storage.

Regulation 1907/2006/EC

## **AeroShell Turbine Oil 308**

Version 4.0 Revision Date 14.08.2015 Print Date 15.08.2015

## **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

Basis for assessment : Information given is based on data on the components and

> the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a

whole, rather than for individual component(s).

exposure

Information on likely routes of : Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

## Acute toxicity

#### **Product:**

Acute oral toxicity : LD50 rat: > 5,000 mg/kg

Remarks: Expected to be of low toxicity:

: Remarks: Not considered to be an inhalation hazard under Acute inhalation toxicity

normal conditions of use.

: LD50 Rabbit: > 5,000 mg/kg Acute dermal toxicity

Remarks: Expected to be of low toxicity:

#### Skin corrosion/irritation

#### **Product:**

Remarks: Expected to be slightly irritating., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

## Serious eye damage/eye irritation

## **Product:**

Remarks: Expected to be slightly irritating.

## Respiratory or skin sensitisation

#### **Product:**

Remarks: For skin sensitisation:, Expected to be a skin sensitizer.

Remarks: For respiratory sensitisation:, Not expected to be a sensitiser.

#### **Components:**

## N-phenyl-1-naphthylamine:

Regulation 1907/2006/EC

## **AeroShell Turbine Oil 308**

Version 4.0 Revision Date 14.08.2015 Print Date 15.08.2015

Remarks: May cause an allergic skin reaction in sensitive individuals.

2,6-di-tert-butyl dimethylamino p-cresol:

Remarks: May cause an allergic skin reaction in sensitive individuals.

## Germ cell mutagenicity

**Product:** 

: Remarks: Not considered a mutagenic hazard.

## Carcinogenicity

**Product:** 

Remarks: Not expected to be carcinogenic.

| Material                                 | GHS/CLP Carcinogenicity Classification |
|--|--|
| Alkaryl amine                            | No carcinogenicity classification.     |
| Triaryl phosphate                        | No carcinogenicity classification.     |
| N-phenyl-1-naphthylamine                 | No carcinogenicity classification.     |
| 2,6-di-tert-butyl dimethylamino p-cresol | No carcinogenicity classification.     |

## Reproductive toxicity

**Product:** 

Remarks: Not expected to impair fertility., Not expected to be a developmental toxicant.

## STOT - single exposure

**Product:** 

Remarks: Not expected to be a hazard.

## STOT - repeated exposure

**Product:** 

Remarks: Not expected to be a hazard.

## **Aspiration toxicity**

Regulation 1907/2006/EC

## **AeroShell Turbine Oil 308**

Version 4.0 Revision Date 14.08.2015 Print Date 15.08.2015

#### **Product:**

Not considered an aspiration hazard.

#### **Further information**

#### **Product:**

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

Summary on evaluation of the CMR properties

Germ cell mutagenicity-

Assessment

: This product does not meet the criteria for classification in

categories 1A/1B.

Carcinogenicity -

Assessment

: This product does not meet the criteria for classification in

categories 1A/1B.

Reproductive toxicity -

Assessment

: This product does not meet the criteria for classification in

categories 1A/1B.

## **SECTION 12: Ecological information**

## 12.1 Toxicity

Basis for assessment : Ecotoxicological data have not been determined specifically

for this product.

Information given is based on a knowledge of the components

and the ecotoxicology of similar products.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test

extract).

**Product:** 

Toxicity to fish (Acute

toxicity)

: Remarks: Expected to be toxic: LL/EL/IL50 > 1 <= 10 mg/l

Toxicity to crustacean (Acute

toxicity)

Remarks: Expected to be toxic: LL/EL/IL50 > 1 <= 10 mg/l

Regulation 1907/2006/EC

## **AeroShell Turbine Oil 308**

Version 4.0 Revision Date 14.08.2015 Print Date 15.08.2015

Toxicity to algae/aquatic plants (Acute toxicity)

: Remarks: Expected to be toxic: LL/EL/IL50 > 1 <= 10 mg/l

Toxicity to fish (Chronic

toxicity)

: Remarks: Data not available

Toxicity to crustacean

(Chronic toxicity)

: Remarks: Data not available

Toxicity to microorganisms

(Acute toxicity)

Remarks: Data not available

**Components:** 

N-phenyl-1-naphthylamine:

M-Factor (Acute aquatic

toxicity)

: 1

12.2 Persistence and degradability

**Product:** 

Biodegradability : Remarks: Expected to be not readily biodegradable., Major

constituents are expected to be inherently biodegradable, but contains components that may persist in the environment.

12.3 Bioaccumulative potential

**Product:** 

Bioaccumulation : Remarks: Contains components with the potential to

bioaccumulate.

Partition coefficient: n-

octanol/water

: Pow: > 6Remarks: (based on information on similar products)

12.4 Mobility in soil

**Product:** 

Mobility : Remarks: Liquid under most environmental conditions., If it

enters soil, it will adsorb to soil particles and will not be

mobile.

Remarks: Floats on water.

12.5 Results of PBT and vPvB assessment

**Product:** 

Assessment : This mixture does not contain any REACH registered

substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects

**Product:** 

Additional ecological

information

: Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities.,

Not expected to have ozone depletion potential,

Regulation 1907/2006/EC

## **AeroShell Turbine Oil 308**

Version 4.0 Revision Date 14.08.2015 Print Date 15.08.2015

photochemical ozone creation potential or global warming

potential.

Poorly soluble mixture., May cause physical fouling of aquatic

organisms.

## **SECTION 13: Disposal considerations**

## 13.1 Waste treatment methods

Product : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water

courses

Contaminated packaging : Dispose in accordance with prevailing regulations, preferably

to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local legislation Waste catalogue

iste catalogue

EU Waste Disposal Code (EWC):

Waste Code

13 02 06\*

Remarks : Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Classification of waste is always the responsibility of the end

user.

Hazardous Waste (England and Wales) Regulations 2005.

## **SECTION 14: Transport information**

#### 14.1 UN number

# Regulation 1907/2006/EC **AeroShell Turbine Oil 308**

14.6 Special precautions for user

| Acrosticii Turbine On 30               |  |                       |
|--|--|-----------------------|
| Version 4.0                            | Revision Date 14.08.2015   | Print Date 15.08.2015 |
| ADR<br>RID<br>IMDG<br>IATA             | : 3082<br>: 3082<br>: 3082<br>: 3082                                       |                       |
| 14.2 Proper shipping name              |  |                       |
| ADR                                    | : ENVIRONMENTALLY HAZARDOUS N.O.S. (N-phenyl-1-naphthylamine and Trianger) | yl phosphate)         |
| RID                                    | : ENVIRONMENTALLY HAZARDOUS N.O.S. (N-phenyl-1-naphthylamine and Triary    | ,                     |
| IMDG                                   | : ENVIRONMENTALLY HAZARDOUS N.O.S. (N-phenyl-1-naphthylamine and Triary    |                       |
| IATA                                   | : ENVIRONMENTALLY HAZARDOUS N.O.S. (N-phenyl-1-naphthylamine and Triary    |                       |
| 14.3 Transport hazard class            | (  | ,                     |
| ADR                                    | : 9  |                       |
| RID                                    | : 9  |                       |
| IMDG                                   | : 9  |                       |
| IATA                                   | : 9  |                       |
| 14.4 Packing group  ADR                |  |                       |
| Packing group                          | : 111  |                       |
| Classification Code                    | : M6   |                       |
| Hazard Identification Number           | : 90   |                       |
| Labels<br><b>RID</b>                   | : 9  |                       |
| Packing group                          | : III  |                       |
| Classification Code                    | : M6   |                       |
| Hazard Identification Number<br>Labels | : 90<br>: 9  |                       |
| IMDG                                   | . 9  |                       |
| Packing group                          | : III  |                       |
| Labels                                 | : 9  |                       |
| IATA                                   |  |                       |
| Packing group                          | : III  |                       |
| Labels                                 | : 9  |                       |
| 14.5 Environmental hazards             |  |                       |
| ADR                                    |  |                       |
| Environmentally hazardous <b>RID</b>   | : yes  |                       |
| Environmentally hazardous              | : yes  |                       |
| IMDG                                   |  |                       |
| Marine pollutant                       | : yes  |                       |

Regulation 1907/2006/EC

## **AeroShell Turbine Oil 308**

Version 4.0 Revision Date 14.08.2015 Print Date 15.08.2015

Remarks : Special Precautions: Refer to Chapter 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category : Not applicable
Ship type : Not applicable
Product name : Not applicable
Special precautions : Not applicable

**Additional Information**: MARPOL Annex 1 rules apply for bulk shipments by sea.

## **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation : Product is not subject to

(Annex XIV) Authorisation under REACH.

Volatile organic compounds : 0 %

Other regulations : Environmental Protection Act 1990 (as amended). Health and

Safety at Work etc. Act 1974. Consumers Protection Act 1987. Pollution Prevention and Control Act 1999. Environment Act 1995. Factories Act 1961. The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment (Amendment) Regulations 2011. Chemicals (Hazard Information and Packaging for Supply) Regulations 2009. Control of Substances Hazardous to Health Regulations 2002 (as amended). Merchant Shipping (Dangerous Goods and Marine Pollutants) Regulations 1997. Reporting of Injuries, Diseases and Dangerous Occurrences Regulations 1995 (as amended). Personal Protective Equipment Regulations 2002. Personal Protective Equipment at Work Regulations 1992. Hazardous Waste (England and Wales) Regulations 2005(as amended). Control of Major Accident Hazards Regulations 1999 (as amended). Renewable Transport Fuel Obligations Order 2007 (as amended). Energy Act 2011. Environmental Permitting (England and Wales) Regulations 2010 (as amended). Waste (England and Wales) Regulations 2011 (as amended). Planning (Hazardous Substances) Act 1990 and associated regulations. The Environmental Protection (Controls on

Ozone-Depleting Substances) Regulations 2011.

## The components of this product are reported in the following inventories:

EINECS : All components listed or polymer exempt.

Regulation 1907/2006/EC

## **AeroShell Turbine Oil 308**

Version 4.0 Revision Date 14.08.2015 Print Date 15.08.2015

TSCA : All components listed.

#### 15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## **SECTION 16: Other information**

#### REGULATION (EC) No 1272/2008 Classification procedure:

Skin sensitisation, Category 1, H317 Expert judgement and weight of evidence

determination.

Chronic aquatic toxicity, Category 2, Expert judgement and weight of evidence

H411 determination.

#### **Full text of H-Statements**

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure

if swallowed.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H412 Harmful to aquatic life with long lasting effects.

## Full text of other abbreviations

Skin Sens.

Acute Tox. Acute toxicity

Aquatic Acute Acute aquatic toxicity
Aquatic Chronic Chronic aquatic toxicity

Eye Irrit. Eye irritation Repr. Reproductive toxicity

STOT RE Specific target organ toxicity - repeated exposure

Skin sensitisation

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this

document can be looked up in reference literature (e.g.

scientific dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial

Hygienists

ADR = European Agreement concerning the International

Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council CLP = Classification Packaging and Labelling

COC = Cleveland Open-Cup

DIN = Deutsches Institut für Normung DMEL = Derived Minimal Effect Level

Version 4.0 Revision Date 14.08.2015 Print Date 15.08.2015

DNEL = Derived No Effect Level

DSL = Canada Domestic Substance List

EC = European Commission

EC50 = Effective Concentration fifty

ECETOC = European Center on Ecotoxicology and

**Toxicology Of Chemicals** 

ECHA = European Chemicals Agency

EINECS = The European Inventory of Existing Commercial

**Chemical Substances** 

EL50 = Effective Loading fifty

ENCS = Japanese Existing and New Chemical Substances

Inventory

EWC = European Waste Code

GHS = Globally Harmonised System of Classification and

Labelling of Chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IC50 = Inhibitory Concentration fifty

IL50 = Inhibitory Level fifty

IMDG = International Maritime Dangerous Goods

INV = Chinese Chemicals Inventory

IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables

KECI = Korea Existing Chemicals Inventory

LC50 = Lethal Concentration fifty

LD50 = Lethal Dose fifty per cent.

LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading

LL50 = Lethal Loading fifty

MARPOL = International Convention for the Prevention of

Pollution From Ships

NOEC/NOEL = No Observed Effect Concentration / No

Observed Effect Level

OE HPV = Occupational Exposure - High Production Volume

PBT = Persistent, Bioaccumulative and Toxic

PICCS = Philippine Inventory of Chemicals and Chemical

Substances

PNEC = Predicted No Effect Concentration

REACH = Registration Evaluation And Authorisation Of

Chemicals

RID = Regulations Relating to International Carriage of

Dangerous Goods by Rail

SKIN\_DES = Skin Designation

STEL = Short term exposure limit

TRA = Targeted Risk Assessment

TSCA = US Toxic Substances Control Act

TWA = Time-Weighted Average

vPvB = very Persistent and very Bioaccumulative

#### **Further information**

Other information : A vertical bar (|) in the left margin indicates an amendment

from the previous version.

Regulation 1907/2006/EC

# **AeroShell Turbine Oil 308**

Version 4.0 Revision Date 14.08.2015 Print Date 15.08.2015

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

20 / 20