

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0
Revision Date: 23.08.2010
Superseded date: 04.06.2009**DOW CORNING(R) AS 7096N SEALANT CLEAR****1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY**

- 1.1 Product name** : DOW CORNING(R) AS 7096N SEALANT CLEAR
- 1.2 Identified uses** : Adhesive, binding agents
Construction materials and additives
- Uses advised against** : None known.
- 1.3 Company** : Dow Corning Europe S.A.
rue Jules Bordet - Parc Industriel - Zone C
B-7180 Seneffe
Belgium
- E-mail address (Safety Data Sheet)** : sdseu@dowcorning.com
- Customer Service** : English Tel: +49 611237507
Deutsch Tel: +49 611237500
Français Tel: +32 64511149
Italiano Tel: +32 64511170
Español Tel: +32 64511163
- Fax: +32 64888683
- 1.4 Emergency Phone Number** : Dow Corning (Barry U.K. 24h) Tel: +44 1446732350
Dow Corning (Wiesbaden 24h) Tel: +49 61122158
Dow Corning (Seneffe 24h) Tel: +32 64 888240

2. HAZARDS IDENTIFICATION**2.1 Classification of the substance or mixture**

According to EU Directives 67/548/EEC or 1999/45/EC:

Not hazardous.

2.2 Label elements**Labelling according to EEC Directive**

S-phrases : S24 Avoid contact with skin.
S51 Use only in well-ventilated areas.

2.3 Other hazards

Contains Trimethoxy(methyl)silane and N-(3-(Trimethoxysilyl)propyl)ethylenediamine. May produce an allergic reaction.

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0
 Revision Date: 23.08.2010
 Superseded date: 04.06.2009

DOW CORNING(R) AS 7096N SEALANT CLEAR

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical characterization: Silicone elastomer

According to EU Directives 67/548/EEC or 1999/45/EC:

Name	CAS-No.	EINECS/ ELINCS No.	REACH Registration Number	Conc. (% w/w)	Classification
Dimethyl siloxane (triethoxysilyl) ethyl-terminated	195158-82-8	Exempt or not available	-	55.0	Substance with a Community workplace exposure limit
Distillates (petroleum), hydrotreated middle	64742-46-7	265-148-2	-	8.0	Substance with a Community workplace exposure limit
Titanium(4+) 2-methylpropan-2-olate	3087-39-6	221-412-9	-	2.5	R10 Xi R36/38

According to Regulation (EC) No. 1272/2008:

Name	CAS-No.	EINECS/ ELINCS No.	REACH Registration Number	Conc. (% w/w)	Classification
Dimethyl siloxane (triethoxysilyl) ethyl-terminated	195158-82-8	Exempt or not available	-	55.0	Substance with a Community workplace exposure limit
Distillates (petroleum), hydrotreated middle	64742-46-7	265-148-2	-	8.0	Substance with a Community workplace exposure limit
Titanium(4+) 2-methylpropan-2-olate	3087-39-6	221-412-9	-	2.5	Flammable liquid: Category 3 - H226 Skin corrosion/irritation: Category 2 - H315 Serious eye damage/eye irritation: Category 2 - H319

For the full text of the R-phrases mentioned in this Section, see Section 16.

For the full text of the H-Statements mentioned in this Section, see Section 16.

CLP classifications are based on all current available data including from known international organizations. These classifications are subject to revision as more information becomes available.

4. FIRST AID MEASURES

4.1 Description of First Aid Measures:

- On contact with eyes** : Flush with water.
- On skin contact** : Flush with water. Wipe off.
- If inhaled** : Remove to fresh air.
- On ingestion** : Obtain medical attention.

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0

Revision Date: 23.08.2010

Superseded date: 04.06.2009

DOW CORNING(R) AS 7096N SEALANT CLEAR**5. FIRE-FIGHTING MEASURES**

- 5.1 Suitable extinguishing media** : On small fires use carbon dioxide (CO₂), dry chemical or water spray. On large fires use dry chemical, foam or water spray (fog). Water can be used to cool fire exposed containers.
- Unsuitable extinguishing media** : None known.
- 5.2 Hazards during fire fighting** : None known.
- Hazardous Combustion Products** : Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Silica. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde. Nitrogen products.
- 5.3 Special protective equipment/procedures** : A self-contained respirator and protective clothing should be worn. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.

6. ACCIDENTAL RELEASE MEASURES

- 6.1 Personal precautions, protective equipment and emergency procedures** : Wear proper protective equipment.
- 6.2 Environmental precautions** : Do not allow large quantities to enter drains or surface waters.
- 6.3 Methods and materials for containment and cleaning up** : Scrape up and place in a container fitted with a lid. The spilled product produces an extremely slippery surface.

7. HANDLING AND STORAGE

- 7.1 Advice on safe handling** : General ventilation is recommended. Local ventilation is recommended. Do not breathe vapour. Avoid skin and eye contact. Do not empty into drains.
- 7.2 Advice on storage** : Do not store with oxidizing agents. Keep container closed and store away from water or moisture.
Storage temperature: minimum -10 °C, maximum 32 °C
- 7.3 Specific uses** : Refer to technical data sheet available on request.

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0

Revision Date: 23.08.2010

Superseded date: 04.06.2009

DOW CORNING(R) AS 7096N SEALANT CLEAR**8. EXPOSURE CONTROLS / PERSONAL PROTECTION****8.1 Control parameters**

Name	CAS-No.	Exposure Limits
Dimethyl siloxane (triethoxysilyl) ethyl-terminated	195158-82-8	1,000 ppm TWA as ethanol 1,920 mg/m ³ TWA as ethanol
Distillates (petroleum), hydrotreated middle	64742-46-7	10 mg/m ³ STEL Oil Mist,mineral 5 mg/m ³ TWA Oil Mist,mineral

8.2 Exposure controls

Engineering Controls : Ventilation : Refer to Section 7.1

Personal protection equipment

Respiratory protection : Suitable respiratory protection should be worn if the product is used in large quantities, confined spaces or in other circumstances where the OEL may be approached or exceeded.
Depending on the working conditions, wear a respiratory mask with filter(s) A or use a self-contained respirator.
The choice of a filter type depends on the amount and type of chemical being handled in the workplace. Regarding filter characteristics, contact your respiratory protection supplier.

Hand protection : Chemical protective gloves or gauntlets should be worn and removed correctly to avoid skin contamination: Silver shield(TM). 4H(TM). Regarding glove's breakthrough time,contact your chemical protective glove supplier.

Eye/face protection : Safety glasses should be worn.

Skin protection : Wear impervious overalls in circumstances where significant skin contact can occur.

Hygiene measures : Exercise good industrial hygiene practice. Wash after handling, especially before eating, drinking or smoking. Remove contaminated clothing immediately.

Additional information : These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

Environmental exposure controls : Refer to section 6 and 12.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form : Paste

Colour : Translucent white

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0

Revision Date: 23.08.2010

Superseded date: 04.06.2009

DOW CORNING(R) AS 7096N SEALANT CLEAR

Odour	:	Alcoholic
Flash point	:	> 100 °C (Closed Cup)
Explosive properties	:	No
Specific Gravity	:	0.98 - 1.05
Oxidizing properties	:	No

The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

10. STABILITY AND REACTIVITY

10.1 Reactivity	:	This product releases methanol.
10.2 Stability	:	Stable under normal usage conditions.
10.3 Possibility of hazardous reactions	:	None known.
10.4 Conditions to avoid	:	None established.
10.5 Materials to avoid	:	Can react with strong oxidising agents. Keep from any possible contact with water. Protect from moisture
10.6 Hazardous decomposition products	:	Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Silica. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde. Nitrogen products.

11. TOXICOLOGICAL INFORMATION**Acute toxicity:**

On contact with eyes	:	May cause temporary discomfort.
On skin contact	:	Large amount in contact with significant skin surface areas may cause systemic adverse effects.
If inhaled	:	May cause dizziness, drowsiness, confusion, headaches, nausea, and at high concentrations, unconsciousness.
On ingestion	:	Forms methanol. Swallowing large amounts may cause systemic adverse effects and blindness.

Chronic toxicity:

On skin contact	:	May cause sensitization of susceptible persons by skin contact. Prolonged or repeated dermal contact may cause systemic adverse effect.
If inhaled	:	Prolonged or repeated inhalation may cause systemic adverse effects.

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0

Revision Date: 23.08.2010

Superseded date: 04.06.2009

DOW CORNING(R) AS 7096N SEALANT CLEAR

- On ingestion** : Repeated swallowing may cause systemic adverse effects.
- Toxicokinetics, metabolism and distribution** : Dangerous amounts can be absorbed through the skin.
- Other Health Hazard Information** : This product contains (a) powder(s) hazardous by inhalation. This is not relevant to the current physical form of the product, which is not in a respirable form.

¹ Based on product test data.

² Based on test data from similar products.

12. ECOLOGICAL INFORMATION**12.1 Ecotoxicity effects**

No adverse effects on aquatic organisms are predicted.

12.2 Persistence and degradability

Solid material, insoluble in water. No adverse effects are predicted.

12.3 Bioaccumulation

No bioaccumulation potential.

12.4 Release to waters / Mobility in soil**Fate and effects in waste water treatment plants:**

No adverse effects on bacteria are predicted.

12.5 Results of PBT and vPvB assessment

Not applicable.

13. DISPOSAL CONSIDERATIONS

- Product and packaging disposal** : Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

14. TRANSPORT INFORMATION**Road / Rail (ADR/RID)**

Not subject to ADR/RID.

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0

Revision Date: 23.08.2010

Superseded date: 04.06.2009

DOW CORNING(R) AS 7096N SEALANT CLEAR**Sea transport (IMDG)**

Not subject to IMDG code.

Air transport (IATA)

Not subject to IATA regulations.

15. REGULATORY INFORMATION**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Status****EINECS** : All ingredients listed, exempt or notified (ELINCS).**IECSC** : All ingredients listed or exempt.**DSL** : Consult your local Dow Corning office.**TSCA** : All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.**KECL** : All ingredients listed, exempt or notified.

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0

Revision Date: 23.08.2010

Superseded date: 04.06.2009

DOW CORNING(R) AS 7096N SEALANT CLEAR**16. OTHER INFORMATION**

This product safety data sheet was prepared in compliance with article 31 and Annex II of the EU REACH Regulation as well as its relevant amendments, on the approximation of laws, regulations and administrative provisions relative to the classification, packaging and labelling of dangerous substances and preparations.

It is the responsibility of persons in receipt of this Product Safety Data Sheet to ensure that the information contained herein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. If the recipient subsequently produces a formulation containing the Dow Corning product, it is the recipient's sole responsibility to ensure the transfer of all relevant information from the Dow Corning Product Safety Data Sheet to their own Product Safety Data Sheet in compliance with article 31 and Annex II of the EU REACH Regulation.

All information and instructions provided in this Safety Data Sheet (SDS) are based on the current state of scientific and technical knowledge at the date indicated on the present SDS. Dow Corning shall not be held responsible for any defect in the product covered by this SDS, should the existence of such defect not be detectable considering the current state of scientific and technical knowledge.

As stated above, this Safety Data Sheet has been prepared in compliance with applicable European law. If you purchase this material outside Europe, where compliance laws may differ, you should receive from your local Dow Corning supplier a SDS applicable to the country in which the product is sold and intended to be used. Please note that the appearance and content of the SDS may vary - even for the same product - between different countries, reflecting the different compliance requirements. Should you have any question, please refer to your local Dow Corning supplier.

Source of information: Internal data and publically available information

R10 Flammable., **R36/38** Irritating to eyes and skin.

H226 Flammable liquid and vapour., **H315** Causes skin irritation., **H319** Causes serious eye irritation.